

Axil 2000-KL Long Run

Line-interactive UPS




The **Axil 2000-KL UPS** is a dependable power protection solution engineered to safeguard critical electrical equipment from voltage fluctuations, power surges, and unexpected outages.

With a robust 2000 VA capacity, it ensures stable and continuous operation for power-demanding systems, making it an excellent choice for offices, server rooms, and home workstations.

A convenient cold start function allows the UPS to power on without a mains connection, enabling quick restoration of essential devices even during a total power failure.

The unit includes RSA 3-pin output sockets for flexible connectivity across various equipment types.

For added convenience and reliability, the bypass function enables direct power delivery while isolating the UPS's internal components - ideal for maintenance or emergency situations.



- AC Input Voltage
- Output Voltage
- Automatic Mode
- Charging Mode
- Alarm Indicator
- AC Mode
- Battery Mode
- Battery Capacity
- Load Level

Features

- ✓ Pure Sine Wave
- ✓ LCD Display
- ✓ Cold Start Function
- ✓ Bypass Function
- ✓ Built-in USB Connector
- ✓ Voltage Stabilizer Function
- ✓ External Batteries

Technical Specification

Axil 2000-KL

Capacity	2000VA / 1600W
----------	----------------

AC MODE

Input Voltage Range	145 ± 5 ~ 275 ± 7 VAC
---------------------	-----------------------

Input Frequency	45 ~ 65Hz
-----------------	-----------

Regulated Output Voltage Range	220 (1 ± 8%) ± 7 VAC
--------------------------------	----------------------

INVERTER MODE

DC Output Voltage Range	220VAC ± 5%
-------------------------	-------------

DC Output Frequency	50 ± 0.5Hz
---------------------	------------

Power Factor	0.8
--------------	-----

Output Wave Form	Pure Sine Wave
------------------	----------------

Transfer Time	Typical 2 ~ 6ms, Max. 10ms
---------------	----------------------------

Overload Capability	Automatically shut down in 60sec with 110% load, shut down in 5sec with 120% load
---------------------	---

Overcurrent Protection	System shuts down automatically within 20ms
------------------------	---

BATTERY

Battery Model	(External Batteries)
---------------	----------------------

DC Voltage	DC 24V (External Batteries)
------------	-----------------------------

Battery Quantity & Capacity	(External Batteries)
-----------------------------	----------------------

Charging Current	5A / 10A
------------------	----------

Charging Period	6 ~ 8 hours recover to 90% capacity
-----------------	-------------------------------------

Battery Protection Point	Adjustable
--------------------------	------------

PHYSICAL

Type	Line-interactive
------	------------------

Socket type	2 x RSA 3-pin sockets
-------------	-----------------------

Installation type	Floor standing (tower)
-------------------	------------------------

Dimensions (D x W x H)	390 x 145 x 210 mm
------------------------	--------------------

Weight	14 kg
--------	-------

Operating Temperature	0 - 40°C
-----------------------	----------

Humidity	10 to 90% non condensing
----------	--------------------------

PROTECTION

1. Auto re-starts when AC recovers
2. Automatic charging (offline charging)
3. Battery low voltage protection
4. Overload & short circuit protection
5. Over current protection (Breaker for AC mode: System automatically shut down within 20ms in inverter mode).

Product specifications are subject to change without notice.



TALK TO US

☎ 0861 000 133

☎ 082 359 7060

☎ 086 540 6273

✉ info@axil.co.za

🌐 www.axil.co.za

📍 KwaZulu-Natal - Durban
Gauteng - Midrand
Cape Town - Montague Gardens

